

C20051

Additional information please contact:

Borr Drilling Management DMCC
 Level 28 Reef Tower, Cluster O
 P.O. Box 36913
 Jumeirah Lakes Towers, Dubai United Arab Emirates
 +971-04-4487501
 marketing@borrdrilling.com - www.borrdrilling.com

Standard Specification Jackup

General Description

Design / Generation T2005 C/5
Constructing Shipyard Compagnie Francaise D'entreprises Metall
Year Entered Service / Significant Upgrades 1982
Classification..... DNV,A1, Self-Elevating Drilling Unit
Flag Liberia
Overall Dimensions.....257 ft.long x 283 ft.wide x 24.6 ft deep
Legs (3) 488 ft. long, Triangular
Drafts 15.21 ft at loadline
Accommodation 96 persons
Displacement.....30,930kips
Variable Deck.....5,156 kips operating / 1,799 kips transit (spud cans full)
Transit Speed up to 4 knots, @ 9,000 hp sea tug
Operating Water Depth 360 ft. designed / 360 ft. outfitted
Maximum Drilling Depth 25,000ft

Drilling Equipment

Derrick Joseph Paris type; 147 ft high with 36 ft x 36 ft base
Hookload Capacity 1,300,000 lbs gross nominal capacity
Cantilever/ Drill floor 45 ft / 11 ft Port & Stbd
Drawworks NOV SSGD-750 Max hook load 1,653 kips with 12 lines. (4) x NOV DC motors suitable for 1.5" drill line
Rotary Table National 37.5" table opening, electric drive, rated 650 mt
Top Drive Varco TDS-8SA Electric 750 mt
Tubular Handling Varco AR3200, 3-1/2" to 9-3/4" OD drill pipe & drill collar
 Make-up torque 100,000ft-lb Break-out torque 120,000ft-lb
Mud Pumps (2) National HEX240 pumps, each driven by 1,275 hp (NOV AC motor) 7,500 psi rated
Solids Control (4) Brandt VSM300 Shale Shakers

Power & Machinery

Main Power (4) Caterpillar 3516B diesel engines rated at 1,900kW at 1,800rpm each with Caterpillar generator rated to 2,607kVA
Emergency Power (1) Caterpillar C18 diesel engine rated at 601kW at 1,200rpm with Caterpillar generator rated to 687kVA

Storage Capacities

Fuel Oil..... 2,378 bbls
Liquid Mud..... 3,560 bbls
Base Oil 642 bbls
Brine..... 1,579 bbls
Drill Water 3,382 bbls
Potable Water 1,987 bbls
Bulk Material (mud + cement) 11,035 cu-ft
Sack Storage 1,506 sacks

BOP & Well Control Equipment

BOP Rams (1) CIW Double "U" rams 20-3/4" 3k psi BOP
BOP Rams (1) CIW Single "U" rams 13-5/8" 15k psi BOP
BOP Rams (1) CIW Double "U" rams 13-5/8" 15k psi BOP
BOP Annular (1) Hydрил MSP 21-1/4" 2k psi annular preventer
BOP Annular (1) CIW Type D 13-5/8" 10k psi annular preventer
BOP Handling (2) Neuhaus hoists, rated 36mt
Diverter Regan KFDJ 500, 37-1/2" diverter rated to 500psi with (2) 12" outlet lines

Mooring Equipment

Mooring Winches (2) B&L electric winches rated at 50,400 lbs pull; (2) ODIM electric winches at 110,231 lbs pull
Anchor Lines 2,296 ft (Fwd) x 2.25" / 2,953 ft (Aft) x 1.25" wire rope
Anchors (2-Fwd) Delta Flipper anchor, 50mt each; (2-Aft) Delta Flipper anchor, 100mt each

Cranes

Cranes (1) Huisman crane, 80mt capacity,145ft boom
 (1) National OS-215 crane, 41mt capacity,130ft boom
 (1) Huisman crane, 60mt capacity,160ft boom

Special Features & Other Information

Helideck Rated for Sirkosky S-61 helicopters. CAP 437



These specifications are intended for general reference purposes only, as actual equipment and specifications may vary based upon subsequent changes, the contract situation and customer needs. All equipment shall be operated and maintained at all times, in compliance with Borr Drilling standard operating manuals, policies and procedures, and within its stated operational limits or continuous rated capacity, in order to assure maximum operational efficiency.

