

# L1112

## Additional information please contact:

Borr Drilling Management DMCC  
Level 28 Reef Tower, Cluster O  
P.O. Box 36913  
Jumeirah Lakes Towers, Dubai United Arab Emirates  
+971-04-4487501  
  
marketing@borrdrilling.com - www.borrdrilling.com

## Standard Specification Jack-up

### General Description

Design / Generation .....	Levingston 111C
Constructing Shipyard .....	Levingston, USA
Year Entered Service / Significant Upgrades .....	1981
Classification.....	ABS,A1, Self-Elevating Drilling Unit
Flag .....	Liberia
Overall Dimensions.....	268 ft.L x 198 ft.W x 22.92 ft.D
Legs .....	(3) 414.52 ft., Triangular
Drafts .....	22.6 ft at loadline
Accommodation .....	90 persons
Displacement.....	19,222.2 kips
Variable Deck.....	3,552 kips operating / 3,072 kips transit (spud cans full)
Transit Speed .....	up to 4 knots, @ 9,000 hp sea tug
Operating Water Depth .....	300 ft. designed / 300 ft. outfitted
Maximum Drilling Depth .....	20,000ft

### Drilling Equipment

Derrick	Lee C Moore type; 160 ft high with 30 ft x 30 ft base
Hookload Capacity	1,230,000 lbs gross nominal capacity
Cantilever/ Drill floor	45 ft / 12 ft Port & Stbd
Drawworks	Oilwell E 3000 Max hook load 1,458 kips with 12 lines. (3) x GE DC motors suitable for 1.5" drill line
Rotary Table	Oilwell A 49.5" table opening, electric drive, rated 650 st
Top Drive	Varco TDs-4S Electric 650 st
Mud Pumps	(2) Oilwell A1700-PT pumps, each driven by 800 hp (GE 752 DC motor) 5,000 psi rated
Solids Control	(3) Derrick FLC 503 (3) Brandt Triple Tandem

### Power & Machinery

Main Power	(3) GM EMD 16-645-E8 diesel engines rated at 1,950hp at 900rpm each with EMD AB-20-6 generator rated to 2,200kW
Emergency Power	(1) Caterpillar D379-B diesel engine rated at 480kW at 1,200rpm with Caterpillar generator rated to 659kVA

### Storage Capacities

Fuel Oil.....	4,567 bbls
Liquid Mud.....	1,897 bbls
Base Oil .....	906 bbls
Drill Water .....	4,764 bbls
Potable Water .....	1,573 bbls
Bulk Material .....	(mud + cement) 6,780 cu-ft
Sack Storage .....	5,000 sacks

### BOP & Well Control Equipment

BOP Rams	(1) Cameron Single "U" rams 13-5/8" 10k psi BOP
BOP Rams	(1) Cameron Double "U" rams 13-5/8" 10k psi BOP
BOP Annular	(1) Hydril GK 13-5/8" 5k psi annular preventer
BOP Handling	(2) Ingersol Rand Herculink 37.5 mt
Diverter	HYDRIL MSP 500, 29.5" 500psi, (2) 12" outlet lines

### Mooring Equipment

Mooring Winches	(2) Skagit electric winches rated at 216,000 lbs pull;
Anchor Lines	(2) x 2,000 ft x 1.5" wire rope
Anchors	(2) Baldt anchor, 12,000 lbs each;

### Cranes

Cranes	(1) Link Belt ABS218A crane, 31mt capacity, 120ft boom (1) Link Belt ABS218A crane, 31mt capacity, 120ft boom
--------	--

### Special Features & Other Information

Helideck	Rated for Sikrosky S-61 helicopters.
----------	--------------------------------------



These specifications are intended for general reference purposes only, as actual equipment and specifications may vary based upon subsequent changes, the contract situation and customer needs. All equipment shall be operated and maintained at all times, in compliance with Borr Drilling standard operating manuals, policies and procedures, and within its stated operational limits or continuous rated capacity, in order to assure maximum operational efficiency.

